



HYUNDAI TRUCK & BUS



All unspecified dimensions are in mm

MODEL - HD45L			MY 2022		
WEIGHT(KG)	GVM	TOTAL	4500 Kg		
	CHASSIS PAYLOAD		~ 2000 Kg		
DIMENSION(mm)	WHEEL BASE		2,810		
	OVER ALL	LENGTH	5,000		
		WIDTH	2,000		
		HEIGHT	3000		
ENGINE	ENGINE TYPE		D4CB		
	TYPE		4 CYLINDER (COMMON RAIL), 4 STROKE, WATER COOLED (TURBO CHARGER), DIRECT INJECTION DIESEL ENGINE		
	DISPLACEMENT(cc)		2497		
	MAX POWER(PS/RPM)		EURO III	115/3800	
	MAX TORQUE(N.m/RPM)		EURO III	26/2000	
TRANSMISSION	TYPE		6 forward and 1 reverse speed. Manual Gear.		
TIRE	TYPE (Tubeless)		SINGLE FRONT (Big), DUAL REAR (Small) + 2 Spare tires		
	FRONT/REAR		Front : 6.5 R16-10PR (+1 Spare) Rear: 5.5 R13-12PR+Spare tire		
SUSPENSION	TYPE		Front/Rear Semi-elliptic , laminated leaf springs with shock absorber		
	SHOCK ABSORBER		Hydraulic double acting acting telescopic type on the FRONT/REAR axle		
CABIN	CAB INTERIOR		Tinted windshield glass (Upper partial)		
			Door Pockets		
			Steering tilt		
			Radio (AM/FM) , AUX , USB (MP3)		
			Driver & Passenger folding type sunvisor		
	CAB EXTERIOR		Tool Box		
			Front & Rear Towing Hook		
			Body colour bumper		
			3 Keys (1+2 Spare Keys)		
	HEATER & AIR CONDITIONER		Wide Rear View Mirror		
			MULTI-SPEED/INTERMITTENT WIPER WITH WASHER		
			MANUAL HEATER, DEFROSTER & AIR CONDITIONER		
			3 SEATS (2+1)		
SEAT		VYNIL TYPE MATERIAL SEAT			
		SEMI-SEALED HEAD LAMP, FRONT & REAR FOG LAMP, SERVICE LAMP CKT			
LAMP		FRONT & REAR COMBINATION LAMP, MARKER LAMP ON DOORS			
		DIGITAL TACHOMETER			
EQUIPMENT		POWER STEERING			
		ABS BRAKE SYSTEM			
BRAKES	ACTUATION		Hydraulic with vacuum servo assistance, dual circuit		
	SERVICE BRAKE		SIZE(mm)	Drum diameter x Lining width x Lining thickness : ø320 x 85 x 10	
EXHAUST BRAKE		Vacuum operated, butterfly valve type			
FUEL TANK		65litres - Steel tank with lock			
ELECTRIC	BATTERY		12V-100AH MF		
	ALTERNATOR		12V-120A		
	STARTER		12V-2.2KW		
Chiller Body	EXT . DIMENSION		LENGTH	3,400	
			HEIGHT	2,100	
			WIDTH	2,000	
	FLOOR		GRP or Aluminium chequered FLOOR (as mentioned in quotation)		
	Interior Temperature		-18°C to +25°C @ambient temperature of 40 °C		
Freezer Unit		Seperate Engine Driven. Nose Mouted			
PU PANEL THICKNESS		100mm			
OTHERS	Tail Lift		This option is included only if mentioned in quotation		
	Spark Arrestor		This option is included only if mentioned in quotation		
	Reverse Sensor & Reverse Horn		This option is included only if mentioned in quotation		
	Wall mounted hook & lock		This option is included only if mentioned in quotation		
	Aluminium Chequered sheet internal finish		This option is included only if mentioned in quotation		
	Towing hook at front & rear		Included (as mentioned in quotation)		
Rear Hook for coupling trailer		This option is included only if mentioned in quotation			