



All unspecified dimensions are in mm

MODEL - HD45L			MY 2022	
WEIGHT(KG)	GVM	TOTAL	4000 Kg	
	CHASSIS PAYLOAD		~ 2000 Kg	
DIMENSION(mm)	WHEEL BASE		2,810	
	OVER ALL	LENGTH	5,000	
		WIDTH	1,900	
		HEIGHT	3000	
ENGINE	ENGINE TYPE		D4CB	
	TYPE		4 CYLINDER (COMMON RAIL), 4 STROKE, WATER COOLED (TURBO CHARGER), DIRECT INJECTION DIESEL ENGINE	
	DISPLACEMENT(cc)		2497	
	MAX POWER(PS/RPM)		EURO III	115/3800
	MAX TORQUE(N.m/RPM)		EURO III	26/2000
TRANSMISSION	TYPE		6 forward and 1 reverse speed. Manual Gear.	
TIRE	TYPE (Tubeless)		SINGLE FRONT (Big), DUAL REAR (Small) + 2 Spare tires	
	FRONT/REAR		Front : 6.5 R16-10PR (+1 Spare) Rear: 5.5 R13-12PR+Spare tire	
SUSPENSION	TYPE		Front/Rear Semi-elliptic , laminated leaf springs with shock absorber	
	SHOCK ABSORBER		Hydraulic double acting acting telescopic type on the FRONT/REAR axle	
CABIN	CAB INTERIOR		Tinted windshield glass (Upper partial)	
			Door Pockets	
			Steering tilt	
			Radio (AM/FM) , AUX , USB (MP3)	
			Driver & Passenger folding type sunvisor	
	CAB EXTERIOR		Tool Box	
			Front & Rear Towing Hook	
			Body colour bumper	
			3 Keys (1+2 Spare Keys)	
	HEATER & AIR CONDITIONER		MULTI-SPEED/INTERMITTENT WIPER WITH WASHER	
			MANUAL HEATER, DEFROSTER & AIR CONDITIONER	
SEAT		3 SEATS (2+1) VYNIL TYPE MATERIAL SEAT		
LAMP		SEMI-SEALED HEAD LAMP, FRONT & REAR FOG LAMP, SERVICE LAMP CKT FRONT & REAR COMBINATION LAMP, MARKER LAMP ON DOORS		
EQUIPMENT		DIGITAL TACHOMETER		
		POWER STEERING		
BRAKES		ACTUATION		
		SERVICE BRAKE		
EXHAUST BRAKE		Hydraulic with vacuum servo assistance, dual circuit		
FUEL TANK		SIZE(mm) Drum diameter x Lining width x Lining thickness : ø320 x 85 x 10		
ELECTRIC		Vacuum operated, butterfly valve type		
BATTERY		65litres - Steel tank with lock		
ALTERNATOR		12V-100AH MF		
STARTER		12V-120A		
Chiller Body		STARTER		
		12V-2.2KW		
		EXT . DIMENSION		
		LENGTH	3,400	
		HEIGHT	2,200	
		WIDTH	2,000	
		INTERNAL VOLUME		11.5 CBM
FLOOR		GRP or Aluminium chequered FLOOR		
Interior Temperature		. +5°C to +25°C @ambient temperature of 40 °C		
Chiller Unit		Vehilce Engine Driven. Nose Mouted		
PU PANEL THICKNESS		100mm		
OTHERS	Tail Lift		This option is included only if mentioned in quotation	
	Spark Arrestor		This option is included only if mentioned in quotation	
	Reverse Sensor & Reverse Horn		This option is included only if mentioned in quotation	
	Wall mounted hook & lock		This option is included only if mentioned in quotation	
	Aluminium Chequered sheet internal finish		This option is included only if mentioned in quotation	
	Towing hook at front & rear		This option is included only if mentioned in quotation	
Rear Hook for coupling trailer		This option is included only if mentioned in quotation		