



All unspecified dimensions are in mm

MODEL - HD45L			LONG WHEEL BASE	
	CHASSIS PAYLOAD		2000 Kg	
DIMENSION(mm)	WHEEL BASE		2,810	
	OVER ALL	LENGTH	5,310	
		WIDTH	1,780	
		HEIGHT	2195	
ENGINE	ENGINE TYPE		D4CB11	
	TYPE	TURBO CHARGER INTERCOOLER, 4 CYLINDER, COMMON RAIL DIESEL INJECTION. EURO 3		
	DISPLACEMENT(cc)	2497		
	MAX POWER(PS/RPM)	EURO III	115/3800	
	MAX TORQUE(N.m/RPM)	EURO III	26/2000	
TRANSMISSION	TYPE	6 forward and 1 reverse speed , 1st to 6th synchromesh, reverse constant-mesh gears. Manual Gear.		
TIRE	TYPE	SINGLE FRONT (<i>Big</i>) , DUAL REAR (<i>Small</i>)		
	FRONT (Single)	6.5R16-10PR {Tubeless}		
	REAR (Dual)	5.5R13-12PR {Tubeless}		
SUSPENSION	TYPE	Front/Rear	Semi-elliptic , laminated leaf springs with shock absorber	
	SHOCK ABSORBER	Hydraulic double acting acting telescopic type on the FRONT/REAR axle		
CABIN	CAB INTERIOR	Tinted windshield glass (Upper partial)		
		Door Pockets		
		Steering tilt		
		Radio (AM/FM) , AUX, USB		
		Driver & Passenger folding type sunvisor		
		Tool Box		
	CAB EXTERIOR	Front & Rear Towing Hook		
		Body colour bumper		
		Wide Rear View Mirror		
		MULTI-SPEED/INTERMITTENT WIPER WITH WASHER		
	HEATER & AIR CONDITIONER	MANUAL HEATER, DEFROSTER & AIR CONDITIONER		
	SEAT	3 SEATS (2+1)		
	LAMP	VYNIL (SIMULATED LEATHER) MATERIAL SEAT		
		SEMI-SEALED HEAD LAMP, FRONT & REAR FOG LAMP, SERVICE LAMP CKT		
EQUIPMENT	FRONT & REAR COMBINATION LAMP, MARKER LAMP ON DOORS			
	DIGITAL TACHOMETER			
	POWER STEERING			
BRAKES	ACTUATION	Hydraulic with vacuum servo assistance, dual circuit		
	SERVICE BRAKE	SIZE(mm)	Drum diameter x Lining width x Lining thickness : ϕ 320 x 85 x 10	
EXHAUST BRAKE	Vacuum operated, butterfly valve type			
FUEL TANK	65litres - Steel tank with lock			
ELECTRIC	BATTERY	12V-100AH MF		
	ALTERNATOR	12V-100AH MF		
	STARTER	12V-2.2KW		
Cargo Body	DIMENSION (mm)	External Dimension:3.5m (L) x 2.05m (W) x 0.4m (H)		