



All unspecified dimensions are in mm

MODEL - HD65			MY 2022	
WEIGHT(KG)	EMPTY VEHICLE WEIGHT	TOTAL	3,800	
	GVM	TOTAL	6,500	
	Chassis PAYLOAD		<b>4,200</b>	
DIMENSION(mm)	WHEEL BASE		3,375	
	OVER ALL	LENGTH	6,500	
		WIDTH	2,100	
		HEIGHT	3100	
ENGINE	ENGINE TYPE		D4DC	
	TYPE	4 INLINE CYLINDER, 4 STROKE, WATER COOLED, DIRECT INJECTION DIESEL ENGINE		
	DISPLACEMENT(cc)	3907		
	MAX POWER(PS/RPM)	EURO I	<b>120/3200</b>	
	MAX TORQUE(N.m/RPM)	EURO I	30/2000	
TRANSMISSION	TYPE	5 forward and 1 reverse speed , 1st to 5th synchromesh, reverse constant-mesh gears. Manual Gear.		
TIRE	TYPE	SINGLE FRONT, DUAL REAR		
	FRONT/REAR	7R16-10PR {6+1 Spare}		
SUSPENSION	TYPE	Front/Rear	Semi-elliptic , laminated leaf springs with shock absorber	
	SHOCK ABSORBER	Hydraulic double acting acting telescopic type on the FRONT/REAR axle		
CABIN	CAB INTERIOR	Tinted windshield glass (Upper partial)		
		Door Pockets, <b>Over head storage</b> area (3 sections)		
		Steering tilt		
		Radio (AM/FM) , AUX		
		Driver & Passenger folding type sunvisor		
	CAB EXTERIOR	Tool Box		
		Front & Rear Towing Hook		
		Body colour bumper		
	HEATER & AIR CONDITIONER		MANUAL HEATER, DEFROSTER & AIR CONDITIONER	
	SEAT	3 SEATS (2+1)		
LAMP	SEMI-SEALED HEAD LAMP, FRONT & REAR FOG LAMP, SERVICE LAMP CKT			
EQUIPMENT	FRONT & REAR COMBINATION LAMP, MARKER LAMP ON DOORS			
	DIGITAL TACHOMETER			
	POWER STEERING			
BRAKES	ACTUATION	Hydraulic with vacuum servo assistance, dual circuit		
	SERVICE BRAKE	SIZE(mm)	Drum diameter x Lining width x Lining thickness : ø320 x 85 x 10	
EXHAUST BRAKE	Vacuum operated, butterfly valve type			
FUEL TANK	100litres - Steel tank with lock			
ELECTRIC	BATTERY	MF 90AH		
	ALTERNATOR	24V-40A		
	STARTER	24V-5.0KW		
100mm PU INSULATED BOX	EXT . DIMENSION	LENGTH	4,400	
		WIDTH	2,100	
		HEIGHT	2,100	
	INT . DIMENSION	LENGTH	4,200	
		WIDTH	1,900	
		HEIGHT	1,900	
	GRP FLOOR (professional finish)	100% water proof. Top layer of anti slip GRP coating		
SIDE DOOR	ON KERB SIDE (1.7mx0.8m) HxW			
FREEZER UNIT	BRAND	THERMOKING		
	MODEL	T560 (12V with Aux.engine & Electric Stand by)		
	Temperature inside compartment	-18°C to +25°C (Pls refer quotation)		